

SUOER

Rebound Tonometer
SW-500



optohellas[®]

Europe & Middle East Representation

SUOER



Rebound Tonometer SW-500

SUOER rebound Tonometer SW-500 is used to measure intraocular pressure, there are two working modes: vertical and horizontal. Wireless data output the principle: when the probe contact the surface of different hardness at a certain speed, it has different reaction of the probe rebounding.

Advantage: high accuracy, portable, without anesthesia, without the cross-infection etc.

Technical data

Measure Range	3mmHg~70mmHg
Precision	$\pm 1.5\text{mmHg}$ ($3\text{mmHg} \leq \text{IOP} \leq 25\text{mmHg}$); $\pm 2.5\text{mmHg}$ ($25\text{mmHg} < \text{IOP} \leq 70\text{mmHg}$);
Measurment Mode	Both vertical and horizontal measurment
Output	Wireless Infrared Thermal Printer
Easy to use	
Small size, Easy to carry	
No need Anesthesia, No Discomfortableness	

SUOER



SUOER OPHTHALMOLOGY

M. Alexandrou 50, 60133 Katerini
Branch: Evelpidon 61-63
11362 Athens, Greece

Tel: +30 23510 79750 / +30 210 5750572
e-mail: info@opto.gr
[http: www.opto.gr](http://www.opto.gr)

Distributed By

optohellas[®]
ΟΦΘΑΛΜΟΛΟΓΙΚΑ ΜΗΧΑΝΗΜΑΤΑ